

EnergyStation 60kWh

Features:

- Easy to install and deploy with large space utilization;
- Unique modular design & flexible function configuration;
- With self-use, peak shifting, forced charging & discharging and other working modes;
- Strong scalability, simple & convenient expansion on both AC and DC sides;



| Model | 3060 | 5060 |
|--|--|-----------------|
| Battery parameters | | |
| Number of battery packs | 12 | 12 |
| Rated voltage | 614.4V | |
| Voltage range | 556.8~662.4V | |
| Rated energy | 60kWh | |
| Max. continuous charging and discharging current | 100A | |
| Communication | RS485/CAN | |
| Cycle life | 6000times (25 °C, 0.5C, 90%DOD, EOL70%) | |
| PV parameters | | |
| Max.PV input power | 39kW | 65kW |
| Rated input voltage | 600VDC | |
| Max.input voltage | 1000VDC | |
| MPPT voltage range | 200~850VDC | |
| PV input current | 36+36+36 (A) | 36+36+36+36 (A) |
| AC side parameters | | |
| AC rated input/output power | 30kVA | 50kVA |
| AC Max. input/output power | 33kVA | 55kVA |
| AC rated input/output current | 45.6A | 75.8A |
| AC Max. input/output power | 60A | 83.3A |
| Voltage | 3L/N/PE; 220/380V; 230/400V | |
| Frequency | 50/60Hz | |
| THDi | ≤3% | |
| Power Factor | 0.8 leading to 0.8 lagging | |
| System parameters | | |
| Dimension (w*h*d) | 1200*2160*750mm | |
| Weight | 860kg | 880kg |
| Communication | CAN/RS485/WiFi/ETH | |
| Warranty | 10years | |
| Expansion | Support in parallel up to 150kW/180kWh | |
| Protection grade | IP55 | |
| Cooling | Air conditioner | |
| Environment temperature | -30~50 °C | |
| Humidity | 10%~95%RH | |
| Altitude | <2000m | |
| Certification | UN38.3, CE, IEC62619 , CEI 0-21, VDE-AR-N 4105 , IEC 62109 | |